

**Low Country Harley-Davidson  
Service Department  
Vehicle Maintenance Schedule**

**TOURING**

Item Serviced	Procedure	1,000 5,000	2,500 7,500	10,000	20,000	30,000	DONE
Engine Oil & Filter	Replace or Inspect Level	R	I	R	R	R	
Oil Lines & Brake Lines	Inspect for leaks	I	I	I	I	I	
Air Cleaner	Inspect and Clean	I/C	I/C	I/C	I/C	I/C	
Tires	Inspect Tread, Check Pressure	I/C	I/C	I/C	I/C	I/C	
Wheel Spokes	Check Tightness	C		C	C	C	
Primary Chaincase Fluid	Replace or Inspect Level	R	I	R	R	R	
Primary Chain	Adjust	A		A	A	A	
Transmission fluid	Replace or Inspect Level	R	I	R	R	R	
Clutch	Adjust	A		A	A	A	
Clutch Cable	Adjust and Lubricate	A/L		A/L	A/L	A/L	
Rear Belt and Sprockets	Inspect, Adjust Belt	I/A	I/A	I/A	I/A	I/A	
Throttle and Enricher Cables	Adjust and Lubricate	A/L		A/L	A/L	A/L	
Clutch and Brake Levers	Lubricate	L	L	L	L	L	
Kick Stand	Adjust and lubricate	A/L		A/L	A/L	A/L	
Fuel Valve, Lines and Fittings	Inspect for Leaks	I	I	I	I	I	
Fuel Tank Filter Screen	Clean or Replace				C/R		
Brake Fluids	Check Levels and Condition	C		C	C	C	
Brake Pads and Discs	Inspect for Wear	I	I	I	I	I	
Brake Components: Caliper Pins, Boots, Bushings	Inspect or Lubricate	I	I	I	L	L	
Shifter Linkage	Inspect or Lubricate	I/L	I/L	I/L	I/L	I/L	
Spark Plugs	Inspect or Replace	I		R	R	R	
Electrical Equipment and Switches	Check Operation, Includes Cruise Control & Sound System	C	C	C	C	C	
Electrical Diagnostic Check	Digital Technician Computer			C	C	C	
<b>All EFI Vehicles Will Receive a Printout Using our Digital Technician Computer Verifying Proper Operation at 10K's</b>							
Engine Idle Speeds	Check and Adjustment	C	C	C	C	C	
Front Fork Oil	Replace				R		
Steering Head Bearings -	Adjust and Lubricate	A/L		A/L	A/L	A/L	
Rear Fork Bearings	Replace				R		
Windshield Bushings	Inspect			I	I	I	
Fuel Door and Saddlebags	Lubricate Hinges and Latches	L	L	L	L	L	
Air Suspension	Check Pressure, Operation	C	C	C	C	C	
Critical Fasteners	Check Tightness	C	C	C	C	C	
Engine Mounts-Stabilizer Links	Inspect			I	I	I	
Battery	Verify Charging and Connections	V	V	V	V	V	
Road Test	Verify Operation of All Components and System Functions	V	V	V	V	V	
Wash	Hot & Soapy with Air Blow Dry	W	W	W	W	W	

R = Replace

I = Inspect

A = Adjust

L = Lubricate

C = Clean

X = Check

V = Verify    W = Wash

With Optional Oil and Filter-----

For Synthetic Lubricant - Add

Pre 2000- Inspect and Repack Wheel Bearings - Add

**Your Service Professional**