

Low Country Harley-Davidson

Service Department

Dyna Models

Vehicle Maintenance Schedule

Item Serviced	Procedure	1,000 5,000	2,500 7,500	10,000	20,000 40,000	25,000 50,000	30,000	DONE
Engine Oil & Filter	Replace or Inspect Level	R	I	R	R	R	R	
Oil Lines & Brake Lines	Inspect for leaks	I	I	I	I	I	I	
Air Cleaner	Inspect and Clean	I	I	R	R	I/R	R	
Tires	Inspect Tread, Check Pressure	I	I	I	I	I	I	
Wheel Spokes	Check Tightness	C/A	C/A	C/A	C/A	C/A	C/A	
Primary Chaincase Fluid	Replace or Inspect Level	R	I	R	R	R	R	
Primary Chain	Adjust (N/A on 06 + Models)	A	C	A	A	A	A	
Transmission fluid	Replace or Inspect Level	R	I	R	R	R	R	
Clutch	Adjust	A		A	A	A	A	
Clutch Cable	Adjust and Lubricate	A/L	I	A/L	A/L	A/L	A/L	
Cam Chain Tensioners	Inspect or Replace at 35K							
Rear Belt and Sprockets	Inspect, Adjust Belt	I/A	I	I/A	I/A	I/A	I/A	
Throttle & Enricher Cables	Adjust and Lubricate	A/L	I	A/L	A/L	A/L	A/L	
Clutch and Brake Levers	Lubricate	L		L	L	L	L	
Kick Stand	Adjust and lubricate	L	L	L	L	L	L	
Fuel Valve, Lines & Fittings	Inspect for Leaks	I	I	I	I	I	I	
Fuel Tank Filter Screen	Clean or Replace					R		
Brake Fluids	Check Levels and Condition	I	I	R	R	I/R	R	
Brake Pads and Discs	Inspect for Wear	I	I	I	I	I	I	
Brake Components: Caliper Pins, Boots, Bushings	Inspect	I	I	I	I	I	I	
Shifter Linkage	Inspect or Lubricate	I/L	I	I/L	I/L	I/L	I/L	
Spark Plugs	Inspect or Replace	I	I	R	R	I/R	R	
Electrical Equipment	Check Operaton	C	C	C	C	C	C	
Electrical Switches	Check Operation	C	C	C	C	C	C	
Electrical Diagnostic Check	Digital Technician Computer			V	V	V	V	
All EFI Vehicles Will Receive a Printout Using our Digital Technician Computer Verifying Proper Operation at 10K's								
Engine Idle Speeds	Check and Adjustment	V	V	V	V	V	V	
Front Fork Oil	Replace				R			
Steering Head Bearings -	Adjust and Lubricate	A		A	A	A	D/I	
Rear Fork Bearings	Repack						I	
Exhaust System	Check All Fasteners	C	C	C	C	C	C	
Windshield Bushings	Inspect	I	I	I	I	I	I	
Critical Fasteners	Check Tightness	C	C	C	C	C	C	
Battery	Verify Charging and Connections	V	V	V	V	V	V	
	Verify Operation of All Components and System Functions							
Road Test		V	V	V	V	V	V	
Wash	Hot & Soapy with Air Blow Dry	W	W	W	W	W	W	

D=Disassemble

C=Check

V = Verify

W = Wash

R = Replace

I = Inspect

A = Adjust

L = Lubricate

With Optional Oil and Filter-----

FOR SYNTHETIC LUBRICANTS ADD \$40

Pre 2000- Inspect and Repack Wheel Bearings Add \$53

Was Your Service Professional