

Low Country Harley-Davidson
Service Department
Vehicle Maintenance Schedule

Tri Glide

Item Serviced	Procedure	1,000 5,000	2,500 7,500	10,000 30,000	20,000 40,000	25,000 50,000	DONE
Engine Oil & Filter	Replace or Inspect Level	R	I	R	R	R	
Oil Lines & Brake Lines	Inspect for leaks	I	I	I	I	I	
Air Cleaner	Inspect, Clean or replace	I	I	R	R	I/R	
Tires	Inspect Tread, Check Pressure	I	I	I	I	I	
Wheel Spokes	Check Tightness	C/A	C/A	C/A	C/A	C/A	
Primary Chaincase Fluid	Replace or Inspect Level	R	I	R	R	R	
Transmission fluid	Replace or Inspect Level	R	I	R	R	R	
Clutch	Adjust	A		A	A	A	
Clutch Cable	Adjust and Lubricate	A/L	I	A/L	A/L	A/L	
Rear Belt and Sprockets	Inspect, Adjust Belt	I/A	I	I/A	I/A	I/A	
Compensator sprocket isolators	Inspect For Wear	I	I	I	I	I	
Cam Chain Tensioners	Inspect or replace at 35K						
Clutch & Brake Lever Pins	Lubricate	L		L	L	L	
Fuel Valve, Lines & Fittings	Inspect for Leaks	I	I	I	I	I	
Parking Brake	Inspect, Adjust	I/A	I	I/A	I/A	I/A	
Fuel Tank Filter	Replace (25K+ 50K)					R	
Brake Fluids	Check Levels, Condition or Flush	I	I	R	R	I/R	
Brake Pads and Discs	Inspect for Wear	I	I	I	I	I	
Brake Components: Caliper Pins, Boots, Bushings	Inspect	I	I	I	I	I	
Shifter Linkage	Inspect and Lubricate	I/L	I	I/L	I/L	I/L	
Spark Plugs	Inspect or Replace	I	I	R	R	I/R	
Electrical Equipment and Switches	Check Operation, Includes Cruise Control & Sound System	C	C	C	C	C	
Electrical Diagnostic Check	Digital Technician Computer			V	V	V	
All EFI Vehicles Will Receive a Printout Using our Digital Technician Computer Verifying Proper Operation at 10K's							
Engine Idle Speeds	Check and Adjustment	V	V	V	V	V	
Front Fork Oil	Replace				R		
Steering Head Bearings -	Adjust/lubricate Replace at 50k	A/L		A/L	A/L	A/L/R	
Hydraulic Steering Damper	Check for leaks, smooth damper action and tightness of mounting fasteners	C	C	C	C	C	
Air Suspension	Check pressure, operation and leakage	C	C	C	C	C	
Rear Fork Bearings	Replace at 50K					R	
Exhaust System	Check All Fasteners	C	C	C	C	C	
Fuel Door & Saddlebags	Lubricate Hinges & Latches	L	I	L	L	L	
Critical Fasteners	Check Tightness	C	C	C	C	C	
Stabilizer Links	Inspect	I	I	I	I	I	
Battery	Verify Charging and Connections	V	V	V	V	V	
Road Test	Verify Operation of All Components and System Functions	V	V	V	V	V	
Wash	Hot & Soapy with Air Blow Dry	W	W	W	W	W	

D=DISASSEMBLE
C=CHECK
V = Verify
W = Wash
R = Replace
I = Inspect
A = Adjust
L = Lubricate

Approximate pricing
 With Optional Oil and Filter-----
FOR SYNTHETIC LUBRICANTS ADD \$50
 Pre 2000- Inspect and Repack Wheel Bearings Add \$53

Was Your Service Professional