

SKID STEERS

■ 2076 ■



mustangmfg.com

serious MUSCLE for serious work



- Advanced 84-hp Yanmar Tier III-certified turbocharged diesel engine keep this machine powered up and ready to work.

- Compact machine width of only 69 inches, brings extra power to small, cramped work spaces.



- Exceptional hydraulic power and high breakout forces drive a variety of attachments.

- Equipped with optional two-speed drive, this unit can reach ground speeds of up to 12.3 mph. Hydraglide® ride control is standard.
- Roomy cabs come standard with a suspension seat, dome light, work lights and choice of controls.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

A Per SAE J818, SAE J732, and ISO 14397
B Unit weight with standard bucket, 175 lbs. (79 kg) operator and full fuel tank

SPECIFICATIONS

	2076	
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	162" (4115)
	B. Height to Hinge Pin - Fully Raised (mm)	123" (3124)
	C. Overall Height to Top of ROPS (mm)	81" (2057)
	D. Ground Clearance to Chassis (mm)	8.0" (203)
	E. Overall Length with Bucket (mm)	131" (3327)
	F. Overall Length without Bucket (mm)	99.5" (2527)
	G. Wheelbase (mm)	42.5" (1080)
	H. Dump Reach at Full Height (mm)	32" (813)
	I. Bucket Rollback at Ground	28°
	J. Dump Angle	37°
	K. Overall Width (mm)	69" (1753)
	L. Bucket Width (mm)	70" (1778)
	M. Clearance Circle - Rear (mm)	66" (1676)
	N. Clearance Circle - Front without Bucket (mm)	50.5" (1283)
	O. Clearance Circle - Front with Bucket (mm)	82" (2083)
	P. Seat to Ground Height (mm)	42" (1067)
	Q. Rollback at Full Height	84°
	R. Dump Height (mm)	93.5" (2375)
	S. Departure Angle	26°
Standard Specification Tire Size	12.00x16.5 HD	
ENGINE	Make	Yanmar
	Model	4TNV98T-Tier III
	Power (kW) @ rpm	84 hp (62.6) @ 2500
	Displacement (L)	202 cu.in. (3.3)
	Maximum Torque (Nm) @ rpm	222 ft.-lbs (301) @ 1850
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	21.8 gpm (82.3)
	High-Flow Hydraulics - Optional (L/min)	36.9 gpm (139.6)
	Filtration	4 micron
	System Relief Pressure (bar)	3000 psi (207)
	Reservoir Capacity (L)	16 gal. (60)
CAPACITIES /WEIGHT	Rated Operating Capacity ^A (kg)	2200 lbs. (998)
	With Optional Counterweight ^A (kg)	2500 lbs. (1134)
	Tipping Load (kg)	4400 lbs. (1995)
	Fuel Tank (L)	19 gal. (71.9)
	Travel Speed - Maximum (km/hr)	12.3 mph (19.8)
	Operating Weight ^B - Approximate (kg)	7480 lbs. (3393)

